ООО "Техэнком" Fujikura

Контрольно-измерительные приборы и оборудование www.tehencom.com No.: B-13M0062 Date of issue: Nov.15, 2013

DATA SHEET

Sheath Clamp CLAMP-S70 series



Sheath Clamps CLAMP-S70 series are used exclusively with Fujikura 70S series and 19S.

2 types of sheath clamps are available for different fiber type and coating diameter.

CLAMP-S70 series

SPECIFICATION			
Model	CLAMP-S70C	CLAMP-S70D	
Applicable number of fiber	Single		
Coating diameter	100 to 3000 µm	900 µm loose tube fiber	
Cleave length	5 to 16 mm	5 to 16 mm	
Fiber holding	Magnetic clamping		
Sheath Clamp setting onto splicer	Sheath clamp is slotted onto the slide stage and secured with a screw.		
Dimensions	42L x 29W x 26H (mm)		
Weight	35g for 1 pair		
Use for	70S/80S, 19S ** CLAMP-S70C is standard item for 70S/80S and 19S.		





900µm

Loose tube fiber





5~16mm

How to set	
A	

Specifications and descriptions are subject to change without prior notice.

CLAMP-S70D

Fujikura Ltd.	1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan		
i ujikula Llu.	Phone : +81-3-5606-1164		
Fujikura Asia Ltd.	438A Alexandra Road, Block A Alexandra Technopark #08-03 Singapore 119967		
Fujikula Asia Llu.	Phone : +65-6-278-8955 Fax : +65-6-278-0965 http://www.fujikura.com.sg		
Eujikura Europo I td	C51 Barwell Buisiness Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK		
Fujikura Europe Ltd.	Phone : +44-20-8240-2000 Fax : +44-20-8240-2010 http://www.fujikura.co.uk		
AFL Telecommunications	260, Parkway East, Duncan, SC29334, USA		
A E leicoommunications	Phone : +1-800-235-3423 Fax : +1-800-926-0007 http://www.aflglobal.com		
Fujikura (China) Co., Ltd. 16th Floor, Shanghai Hang Seng Bank Tower, 1000 Lujiazui Ring Road, Pudong New A Shanghai 200120, CHINA Phone : +86-21-6841-2070 http://www.fujikura.com.cn			